


## Barrel (Tone Chamber) Mandrel Set Up





## **Materials:** Mandrel Setup (Barrel): Assembly: 1) Load large 5/8" OD rubber expansion bushings, 1) Insert the reed assembly into the 1) Game Call Kit 3000 washers and brass tubes as depicted. (Fig. 1) barrel. 2) 5/8" bushings set 3000B 5/8" 2) If possible corners of blanks should be removed using a band saw or similar tool to aid in turning. 3) Reed Kit 3061 3) Place predrilled barrel on mandrel and center over 4) Wood Blank bushings. Tighten knurled nut until blank will not slide on approx. 1 1/2 x 4 rubber bushings. Extra spacers may be necessary, some (drilled 41/64") 7mm mandrels vary in length. 5) Small set turning 4) Make sure your live center is properly placed in the tools end of the mandrel. 6) 7mm mandrel 5) Coyote Howler designs can vary just as the people with appropriate who turn them. We have included drawing of some of the Morse taper more popular designs. See back of this sheet. 7) Sanding rolls, 4 pk. 6) If a lanyard is to be used remember to cut a small cove 1120 (groove) approximately 3/16" deep for the cord to rest in. 8) HUT PPP™ combo 7) On each end of the barrel you will need to round over 109, Crystal Coat™ the openings: the mouth end for comfort and the reed 104, or finish of assembly end for easy insertion. your choice. 8) Sand and finish with HUT PPP™ combo, Crystal Coat<sup>™</sup>, or finish of your choice.